

Patch cords are used in any cable system and are designed for the connection of communication lines with active network equipments, and also for connecting of computers in the workplace to the network device. They provide high connection reliability and allow to quickly change to any connection needs.

Patch cords are made from stranded cables, terminated with connectors such as RJ45 /8P8C compliant with T568B standard. NIKOMAX patch cord connectors are protected by boot cover, which significantly increases service life of a patch cord with latch protection.

Each NIKOMAX Category 6 patch cord and above are checked 100% with Fluke DTX during production. This ensures both performance and full compliance with the most stringent requirements of large reserves of transmission characteristics and reliable performance throughout the life cycle.



✓ Delta Certified :
NMC-PC4SA55B-XXX-C-GY,
NMC-PC4SE55B-XXX-C-GY,
NMC-PC4UE55B-XXX-C-GY

✓ Fluke Tested

✓ RoHS & REACH Compliant

Gold-plated contacts (50 micro-inch)
Not less than 750 connection cycles

Special design minimizes
crosstalk in the connector

Snagless design prevents
cracking and breaking

The minimal form factor,
Do not increase connector size


S/FTP, Cat.6A, RJ45-RJ45

S/FTP, Cat.6, RJ45-RJ45


F/UTP, Cat.5e, RJ45-RJ45

U/UTP, Cat.6, RJ45-RJ45


U/UTP, Cat.5e, RJ45-RJ45




S/FTP



F/UTP



U/UTP



U/UTP



NMC-PC4SA55B-XXX-C-ZZ - LSZH
NMC-PC4SA55B-XXX-ZZ - PVC
S/FTP, Cat.6A, RJ45-RJ45



NMC-PC4SE55B-XXX-C-ZZ - LSZH
NMC-PC4SE55B-XXX-GY - PVC
S/FTP, Cat.6, RJ45-RJ45



NMC-PC4SD55B-XXX-C-GY - LSZH
NMC-PC4SD55B-XXX-GY - PVC
F/UTP, Cat.5e, RJ45-RJ45



NMC-PC4UE55B-XXX-C-ZZ - LSZH
NMC-PC4UE55B-XXX-ZZ - PVC
U/UTP, Cat.6, RJ45-RJ45



NMC-PC4UD55B-XXX-C-ZZ - LSZH
NMC-PC4UD55B-XXX-GY - PVC
U/UTP, Cat.5e, RJ45-RJ45

Legend:

XXX – Length (005 – 0.5 m, 010 – 1 m...)

ZZ – Jacket color:

GY – Gray

BK – Black

WT – White

RD – Red

YL – Yellow

GN – Green

BL – Blue

Technical Specification for LSZH shielded Patch Cords

Part Number	NMC-PC4SA55B-XXX-C-ZZ	NMC-PC4SE55B-XXX-C-ZZ	NMC-PC4SD55B-XXX-C-GY
Type of connector	2xRJ45/8P8C		
Plating	Gold (50 micro-inch)		
Wiremap	T568B on both end		
Protective cap	Latch protector		
Category	6 _A	6	5e
Bandwidth (MHz)	500 MHz	250 MHz	100 MHz
Type	Shielded		
Type of cable	S/FTP	S/FTP	F/UTP
Shielding Design	The internal shielding: polyester aluminum foil with 100% coverage, individual for each pair. Overall shielding: braid of tinned copper wires 16x5x0.1 mm cover an area not less than 55%		Shielding Sharing: polyester aluminum foil, 100% coverage, laid in contact with drain wire.
Number of pairs	4		
Type of conductor	Stranded		
Diameter of wire	26 AWG (7 x 0.165 ± 0.01 mm)		
Material of conductor insulation	Foamed polyethylene (PE foam)		Polyethylene (PE)
Material of ourter jacket	LSZH		
Outer diameter of jacket	6.2 ± 0.2 mm	6.2 ± 0.1 mm	6 ± 0.2 mm
Jacket color	7 colors		Gray
Compliance	ISO/IEC 11801, EN 50173 & ANSI/TIA-568-C.2, ROHS, REACH		
Application	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 10GBASE-T (For Cat.6A & 6), ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive		
Temperature range	Storage -20 to +60°C, Installation from 0 to +50°C, Operating from -20 to +50°C		
Warranty	1 Year		
Packaging	Plastic Bag		

Technical Specification for LSZH unshielded Patch Cords

Part Number	NMC-PC4UE55B-XXX-C-ZZ	NMC-PC4UD55B-XXX-C-ZZ
Type of connector	2xRJ45/8P8C	
Plating	Gold (50 micro-inch)	
Wiremap	T568B on both end	
Protective cap	Latch protector	
Category	6	5e
Bandwidth (MHz)	250 MHz	100 MHz
Type	Unshielded	
Cable Type	U/UTP	
Number of pairs	4	
Type of conductor	Stranded	
Diameter of wire (mm)	24 AWG (7 x 0.205 ± 0.01 mm)	
Material of conductor insulation	Polyethylene (PE)	
Material of ourter jacket	LSZH	
Outer diameter of jacket	6 ± 0.2 mm	5.5 ± 0.1 mm
Jacket color	7 colors	
Compliance	ISO/IEC 11801, EN 50173 & ANSI/TIA-568-C.2, ROHS, REACH	
Application	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive	
Temperature range	Storage -20 to +60°C, Installation from 0 to +50°C, Operating from -20 to +50°C	
Warranty	1 Year	
Packaging	Plastic bag	

The manufacturer reserves the right to alter the appearance and characteristics of the product, without compromising the product's functionality

Technical Specification for PVC shielded Patch Cords

Part Number	NMC-PC4SA55B- XXX-ZZ	NMC-PC4SE55B- XXX-GY	NMC-PC4SD55B- XXX-GY
Type of connector	2xRJ45/8P8C		
Plating	Gold (50 micro-inch)		
Wiremap	T568B on both end		
Protective cap	Latch protector		
Category	6 _A	6	5e
Bandwidth (MHz)	500 MHz	250 MHz	100 MHz
Type	Shielded		
Type of cable	S/FTP	S/FTP	F/UTP
Shielding design	The internal shielding: polyester aluminum foil with 100% coverage, individual for each pair. Overall shielding: braid of tinned copper wires 16x5x0.1 mm cover an area not less than 55%		Shielding Sharing: polyester aluminum foil, 100% coverage, laid in contact with drain wire.
Number of pairs	4		
Type of conductor	Stranded		
Diameter of wire (mm)	26 AWG (7 x 0.165 ± 0.01 mm)		
Material of conductor insulation	Foamed Polyethylene (PE foam)		Polyethylene (PE)
Material of outer shell	Fire-resistant polyvinyl chloride (FR-PVC)		
Outer diameter of jacket	6.2 ± 0.3 mm	6.2 ± 0.2 mm	6 ± 0.1 mm
Jacket color	7 colors	Gray	
Compliance	ISO/IEC 11801, EN 50173 & ANSI/TIA-568-C.2, ROHS		
Application	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 10GBASE-T (For Cat.6A & 6), ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive		
Temperature range	Storage -20 to +60°C, Installation from 0 to +50°C, Operating from -20 to + 50°C		
Warranty	1 Year		
Packaging	Plastic Bag		

Technical Specification for PVC unshielded Patch Cords

Part Number	NMC-PC4UE55B-XXX-ZZ	NMC-PC4UD55B-XXX-GY
Type of connector	2xRJ45/8P8C	
Plating	Gold (50 micro-inch)	
Wiremap	T568B on both end	
Protective cap	Latch protector	
Category	6	5e
Bandwidth (MHz)	250 MHz	100 MHz
Type	Unshielded	
Cable Type	U/UTP	
Number of pairs	4	
Type of conductor	Stranded	
Diameter of wire (mm)	24 AWG (7 x 0.205 ± 0.01 mm)	
Material of conductor insulation	Polyethylene (PE)	
Material of ourter jacket	Fire-resistant polyvinyl chloride (FR-PVC)	
Outer diameter of jacket	6 ± 0.2 mm	5.5 ± 0.1 mm
Jacket color	7 colors	Gray
Compliance	ISO/IEC 11801, EN 50173 & ANSI/TIA-568-C.2, ROHS, REACH	
Application	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive	
Temperature range	Storage -20 to +60°C, Installation from 0 to +50°C, Operating from -20 to +50°C	
Warranty	1 Year	
Packaging	Plastic bag	

The manufacturer reserves the right to alter the appearance and characteristics of the product, without compromising the product's functionality

Ordering Table for LSZH shielded Patch Cords

Part Number	Type	Cat.	Length, m	Individual package		Collective package			Freight package		
				Volume, m ³	Weight, kg	Q'ty	Volume, m ³	Weight, kg	Q'ty	Dimension, mm	Weight, kg
NMC-PC4SA55B-003-C-ZZ	S/FTP	6 _A	0.3			10 pcs.				520x420x290	
NMC-PC4SA55B-005-C-ZZ	S/FTP	6 _A	0.5	0.000254	0.043	10 pcs.	0.002536	0.431	200 pcs.	520x420x290	9.6
NMC-PC4SA55B-010-C-ZZ	S/FTP	6 _A	1.0	0.000338	0.058	10 pcs.	0.003376	0.585	150 pcs.	520x420x290	9.8
NMC-PC4SA55B-015-C-ZZ	S/FTP	6 _A	1.5	0.000422	0.079	10 pcs.	0.004224	0.788	120 pcs.	520x420x290	10.2
NMC-PC4SA55B-020-C-ZZ	S/FTP	6 _A	2.0	0.000506	0.102	10 pcs.	0.005064	1.022	100 pcs.	520x420x290	11.2
NMC-PC4SA55B-030-C-ZZ	S/FTP	6 _A	3.0	0.000634	0.148	10 pcs.	0.006336	1.480	80 pcs.	520x420x290	12.8
NMC-PC4SA55B-050-C-ZZ	S/FTP	6 _A	5.0	0.001014	0.230	10 pcs.	0.010136	2.296	50 pcs.	520x420x290	12.5
NMC-PC4SA55B-075-C-ZZ	S/FTP	6 _A	7.5	0.001266	0.344	10 pcs.	0.012664	3.438	40 pcs.	520x420x290	14.8
NMC-PC4SA55B-100-C-ZZ	S/FTP	6 _A	10.0	0.001448	0.422	10 pcs.	0.014480	4.223	35 pcs.	520x420x290	15.8
NMC-PC4SA55B-150-C-ZZ	S/FTP	6 _A	15.0			10 pcs.				520x420x290	
NMC-PC4SA55B-200-C-ZZ	S/FTP	6 _A	20.0			10 pcs.				520x420x290	
NMC-PC4SE55B-003-C-ZZ	S/FTP	6	0.3			10 pcs.				520x420x290	
NMC-PC4SE55B-005-C-ZZ	S/FTP	6	0.5	0.000254	0.043	10 pcs.	0.002536	0.431	200 pcs.	520x420x290	9.6
NMC-PC4SE55B-010-C-ZZ	S/FTP	6	1.0	0.000338	0.058	10 pcs.	0.003376	0.585	150 pcs.	520x420x290	9.8
NMC-PC4SE55B-015-C-ZZ	S/FTP	6	1.5	0.000422	0.079	10 pcs.	0.004224	0.788	120 pcs.	520x420x290	10.2
NMC-PC4SE55B-020-C-ZZ	S/FTP	6	2.0	0.000506	0.102	10 pcs.	0.005064	1.022	100 pcs.	520x420x290	11.2
NMC-PC4SE55B-030-C-ZZ	S/FTP	6	3.0	0.000634	0.148	10 pcs.	0.006336	1.480	80 pcs.	520x420x290	12.8
NMC-PC4SE55B-050-C-ZZ	S/FTP	6	5.0	0.001014	0.230	10 pcs.	0.010136	2.296	50 pcs.	520x420x290	12.5
NMC-PC4SE55B-075-C-ZZ	S/FTP	6	7.5	0.001266	0.344	10 pcs.	0.012664	3.438	40 pcs.	520x420x290	14.8
NMC-PC4SE55B-100-C-ZZ	S/FTP	6	10.0	0.001448	0.422	10 pcs.	0.014480	4.223	35 pcs.	520x420x290	15.8
NMC-PC4SE55B-150-C-ZZ	S/FTP	6	15.0			10 pcs.				520x420x290	
NMC-PC4SE55B-200-C-ZZ	S/FTP	6	20.0			10 pcs.				520x420x290	
NMC-PC4SD55B-003-C-GY	F/UTP	5e	0.3			10 pcs.				520x420x290	
NMC-PC4SD55B-005-C-GY	F/UTP	5e	0.5	0.000254	0.034	10 pcs.	0.002536	0.339	200 pcs.	520x420x290	7.8
NMC-PC4SD55B-010-C-GY	F/UTP	5e	1.0	0.000338	0.056	10 pcs.	0.003376	0.561	150 pcs.	520x420x290	9.4
NMC-PC4SD55B-015-C-GY	F/UTP	5e	1.5	0.000422	0.075	10 pcs.	0.004224	0.751	120 pcs.	520x420x290	10.0
NMC-PC4SD55B-020-C-GY	F/UTP	5e	2.0	0.000506	0.090	10 pcs.	0.005064	0.898	100 pcs.	520x420x290	10.0
NMC-PC4SD55B-030-C-GY	F/UTP	5e	3.0	0.000634	0.125	10 pcs.	0.006336	1.253	80 pcs.	520x420x290	11.0
NMC-PC4SD55B-050-C-GY	F/UTP	5e	5.0	0.000845	0.192	10 pcs.	0.008448	1.920	60 pcs.	520x420x290	12.5
NMC-PC4SD55B-075-C-GY	F/UTP	5e	7.5	0.001266	0.276	10 pcs.	0.012664	2.760	40 pcs.	520x420x290	12.0
NMC-PC4SD55B-100-C-GY	F/UTP	5e	10.0	0.001266	0.380	10 pcs.	0.012664	3.803	40 pcs.	520x420x290	16.2
NMC-PC4SD55B-150-C-GY	F/UTP	5e	15.0			10 pcs.				520x420x290	
NMC-PC4SD55B-200-C-GY	F/UTP	5e	20.0			10 pcs.				520x420x290	

Ordering Table for LSZH unshielded Patch Cords

Part Number	Type	Cat.	Length, m	Individual package		Collective package			Freight package		
				Volume, m ³	Weight, kg	Q'ty	Volume, m ³	Weight, kg	Q'ty	Dimensions, mm	Weight, kg
NMC-PC4UE55B-003-C-ZZ	U/UTP	6	0.3	0.000211	0.028	10 pcs.	0.002100	0.281	300 pcs.	520x420x290	8.5
NMC-PC4UE55B-005-C-ZZ	U/UTP	6	0.5	0.000253	0.035	10 pcs.	0.002533	0.354	250 pcs.	520x420x290	9.9
NMC-PC4UE55B-010-C-ZZ	U/UTP	6	1.0	0.000338	0.055	10 pcs.	0.003376	0.550	150 pcs.	520x420x290	9.3
NMC-PC4UE55B-015-C-ZZ	U/UTP	6	1.5	0.000338	0.074	10 pcs.	0.003376	0.739	150 pcs.	520x420x290	12.1
NMC-PC4UE55B-020-C-ZZ	U/UTP	6	2.0	0.000422	0.093	10 pcs.	0.004224	0.934	120 pcs.	520x420x290	12.2
NMC-PC4UE55B-030-C-ZZ	U/UTP	6	3.0	0.000506	0.132	10 pcs.	0.005064	1.315	100 pcs.	520x420x290	14.2
NMC-PC4UE55B-050-C-ZZ	U/UTP	6	5.0	0.000845	0.207	10 pcs.	0.008448	2.065	60 pcs.	520x420x290	13.4
NMC-PC4UE55B-075-C-ZZ	U/UTP	6	7.5	0.001266	0.334	10 pcs.	0.012664	3.338	40 pcs.	520x420x290	14.4
NMC-PC4UE55B-100-C-ZZ	U/UTP	6	10.0	0.001448	0.410	10 pcs.	0.014480	4.100	35 pcs.	520x420x290	15.4
NMC-PC4UE55B-150-C-ZZ	U/UTP	6	15.0	0.002200	0.570	10 pcs.	0.02200	5.701	25 pcs.	520x420x290	14.0
NMC-PC4UE55B-200-C-ZZ	U/UTP	6	20.0	0.002200	0.780	10 pcs.	0.02200	7.801	15 pcs.	520x420x290	13.3
NMC-PC4UD55B-003-C-ZZ	U/UTP	5e	0.3	0.000175	0.030	10 pcs.	0.001750	0.301	360 pcs.	520x420x290	8.68
NMC-PC4UD55B-005-C-ZZ	U/UTP	5e	0.5	0.000211	0.031	10 pcs.	0.002110	0.310	300 pcs.	520x420x290	10.3
NMC-PC4UD55B-010-C-ZZ	U/UTP	5e	1.0	0.000254	0.048	10 pcs.	0.002536	0.484	200 pcs.	520x420x290	10.7
NMC-PC4UD55B-015-C-ZZ	U/UTP	5e	1.5	0.000338	0.067	10 pcs.	0.003376	0.672	150 pcs.	520x420x290	11.1
NMC-PC4UD55B-020-C-ZZ	U/UTP	5e	2.0	0.000317	0.081	10 pcs.	0.003168	0.805	160 pcs.	520x420x290	13.9
NMC-PC4UD55B-030-C-ZZ	U/UTP	5e	3.0	0.000422	0.106	10 pcs.	0.004224	1.062	120 pcs.	520x420x290	13.7
NMC-PC4UD55B-050-C-ZZ	U/UTP	5e	5.0	0.000634	0.183	10 pcs.	0.006336	1.825	80 pcs.	520x420x290	15.6
NMC-PC4UD55B-075-C-ZZ	U/UTP	5e	7.5	0.001266	0.266	10 pcs.	0.012664	2.655	40 pcs.	520x420x290	11.6
NMC-PC4UD55B-100-C-ZZ	U/UTP	5e	10.0	0.001448	0.351	10 pcs.	0.014480	3.506	35 pcs.	520x420x290	13.3
NMC-PC4UD55B-150-C-ZZ	U/UTP	5e	15.0	0.003128	0.510	10 pcs.	0.031281	5.100	25 pcs.	520x420x290	13.1
NMC-PC4UD55B-200-C-ZZ	U/UTP	5e	20.0	0.003255	0.605	10 pcs.	0.032551	6.050	15 pcs.	520x420x290	14.2

Ordering Table for PVC shielded Patch Cords

Part Number	Type	Cat.	Length, m	Individual package		Collective package			Freight package		
				Volume, m ³	Weight, kg	Q'ty	Volume, m ³	Weight, kg	Q'ty	Dimensions, mm	Weight, kg
NMC-PC4SA55B-003-ZZ	S/FTP	6 _A	0.3			10 pcs.				520x420x290	
NMC-PC4SA55B-005-ZZ	S/FTP	6 _A	0.5	0.000254	0.043	10 pcs.	0.002536	0.431	200 pcs.	520x420x290	9.6
NMC-PC4SA55B-010-ZZ	S/FTP	6 _A	1.0	0.000338	0.058	10 pcs.	0.003376	0.585	150 pcs.	520x420x290	9.8
NMC-PC4SA55B-015-ZZ	S/FTP	6 _A	1.5	0.000422	0.079	10 pcs.	0.004224	0.788	120 pcs.	520x420x290	10.2
NMC-PC4SA55B-020-ZZ	S/FTP	6 _A	2.0	0.000506	0.102	10 pcs.	0.005064	1.022	100 pcs.	520x420x290	11.2
NMC-PC4SA55B-030-ZZ	S/FTP	6 _A	3.0	0.000634	0.148	10 pcs.	0.006336	1.480	80 pcs.	520x420x290	12.8
NMC-PC4SA55B-050-ZZ	S/FTP	6 _A	5.0	0.001014	0.230	10 pcs.	0.010136	2.296	50 pcs.	520x420x290	12.5
NMC-PC4SA55B-075-ZZ	S/FTP	6 _A	7.5	0.001266	0.344	10 pcs.	0.012664	3.438	40 pcs.	520x420x290	14.8
NMC-PC4SA55B-100-ZZ	S/FTP	6 _A	10.0	0.001448	0.422	10 pcs.	0.014480	4.223	35 pcs.	520x420x290	15.8
NMC-PC4SA55B-150-ZZ	S/FTP	6 _A	15.0			10 pcs.				520x420x290	
NMC-PC4SA55B-200-ZZ	S/FTP	6 _A	20.0			10 pcs.				520x420x290	
NMC-PC4SE55B-003-GY	S/FTP	6	0.3			10 pcs.				520x420x290	
NMC-PC4SE55B-005-GY	S/FTP	6	0.5	0.000254	0.043	10 pcs.	0.002536	0.431	200 pcs.	520x420x290	9.6
NMC-PC4SE55B-010-GY	S/FTP	6	1.0	0.000338	0.058	10 pcs.	0.003376	0.585	150 pcs.	520x420x290	9.8
NMC-PC4SE55B-015-GY	S/FTP	6	1.5	0.000422	0.079	10 pcs.	0.004224	0.788	120 pcs.	520x420x290	10.2
NMC-PC4SE55B-020-GY	S/FTP	6	2.0	0.000506	0.102	10 pcs.	0.005064	1.022	100 pcs.	520x420x290	11.2
NMC-PC4SE55B-030-GY	S/FTP	6	3.0	0.000634	0.148	10 pcs.	0.006336	1.480	80 pcs.	520x420x290	12.8
NMC-PC4SE55B-050-GY	S/FTP	6	5.0	0.001014	0.230	10 pcs.	0.010136	2.296	50 pcs.	520x420x290	12.5
NMC-PC4SE55B-075-GY	S/FTP	6	7.5	0.001266	0.344	10 pcs.	0.012664	3.438	40 pcs.	520x420x290	14.8
NMC-PC4SE55B-100-GY	S/FTP	6	10.0	0.001448	0.422	10 pcs.	0.014480	4.223	35 pcs.	520x420x290	15.8
NMC-PC4SE55B-150-GY	S/FTP	6	15.0			10 pcs.				520x420x290	
NMC-PC4SE55B-200-GY	S/FTP	6	20.0			10 pcs.				520x420x290	
NMC-PC4SD55B-003-GY	F/UTP	5e	0.3			10 pcs.				520x420x290	
NMC-PC4SD55B-005-GY	F/UTP	5e	0.5	0.000254	0.034	10 pcs.	0.002536	0.339	200 pcs.	520x420x290	7.8
NMC-PC4SD55B-010-GY	F/UTP	5e	1.0	0.000338	0.056	10 pcs.	0.003376	0.561	150 pcs.	520x420x290	9.4
NMC-PC4SD55B-015-GY	F/UTP	5e	1.5	0.000422	0.075	10 pcs.	0.004224	0.751	120 pcs.	520x420x290	10.0
NMC-PC4SD55B-020-GY	F/UTP	5e	2.0	0.000506	0.090	10 pcs.	0.005064	0.898	100 pcs.	520x420x290	10.0
NMC-PC4SD55B-030-GY	F/UTP	5e	3.0	0.000634	0.125	10 pcs.	0.006336	1.253	80 pcs.	520x420x290	11.0
NMC-PC4SD55B-050-GY	F/UTP	5e	5.0	0.000845	0.192	10 pcs.	0.008448	1.920	60 pcs.	520x420x290	12.5
NMC-PC4SD55B-075-GY	F/UTP	5e	7.5	0.001266	0.276	10 pcs.	0.012664	2.760	40 pcs.	520x420x290	12.0
NMC-PC4SD55B-100-GY	F/UTP	5e	10.0	0.001266	0.380	10 pcs.	0.012664	3.803	40 pcs.	520x420x290	16.2
NMC-PC4SD55B-150-GY	F/UTP	5e	15.0			10 pcs.				520x420x290	
NMC-PC4SD55B-200-GY	F/UTP	5e	20.0			10 pcs.				520x420x290	

Ordering Table for PVC unshielded Patch Cords

Part Number	Type	Cat.	Length, m	Individual package		Collective package			Freight package		
				Volume, m ³	Weight, kg	Q'ty	Volume, m ³	Weight, kg	Q'ty	Dimensions, mm	Weight, kg
NMC-PC4UE55B-003-ZZ	U/UTP	6	0.3	0.000211	0.028	10 pcs.	0.002100	0.281	300 pcs.	520x420x290	8.5
NMC-PC4UE55B-005-ZZ	U/UTP	6	0.5	0.000253	0.035	10 pcs.	0.002533	0.354	250 pcs.	520x420x290	9.9
NMC-PC4UE55B-010-ZZ	U/UTP	6	1.0	0.000338	0.055	10 pcs.	0.003376	0.550	150 pcs.	520x420x290	9.3
NMC-PC4UE55B-015-ZZ	U/UTP	6	1.5	0.000338	0.074	10 pcs.	0.003376	0.739	150 pcs.	520x420x290	12.1
NMC-PC4UE55B-020-ZZ	U/UTP	6	2.0	0.000422	0.093	10 pcs.	0.004224	0.934	120 pcs.	520x420x290	12.2
NMC-PC4UE55B-030-ZZ	U/UTP	6	3.0	0.000506	0.132	10 pcs.	0.005064	1.315	100 pcs.	520x420x290	14.2
NMC-PC4UE55B-050-ZZ	U/UTP	6	5.0	0.000845	0.207	10 pcs.	0.008448	2.065	60 pcs.	520x420x290	13.4
NMC-PC4UE55B-075-ZZ	U/UTP	6	7.5	0.001266	0.334	10 pcs.	0.012664	3.338	40 pcs.	520x420x290	14.4
NMC-PC4UE55B-100-ZZ	U/UTP	6	10.0	0.001448	0.410	10 pcs.	0.014480	4.100	35 pcs.	520x420x290	15.4
NMC-PC4UE55B-150-ZZ	U/UTP	6	15.0	0.002200	0.570	10 pcs.	0.02200	5.701	25 pcs.	520x420x290	14.0
NMC-PC4UE55B-200-ZZ	U/UTP	6	20.0	0.002200	0.780	10 pcs.	0.02200	7.801	15 pcs.	520x420x290	13.3
NMC-PC4UD55B-003-GY	U/UTP	5e	0.3	0.000175	0.030	10 pcs.	0.001750	0.301	360 pcs.	520x420x290	8.68
NMC-PC4UD55B-005-GY	U/UTP	5e	0.5	0.000211	0.031	10 pcs.	0.002110	0.310	300 pcs.	520x420x290	10.3
NMC-PC4UD55B-010-GY	U/UTP	5e	1.0	0.000254	0.048	10 pcs.	0.002536	0.484	200 pcs.	520x420x290	10.7
NMC-PC4UD55B-015-GY	U/UTP	5e	1.5	0.000338	0.067	10 pcs.	0.003376	0.672	150 pcs.	520x420x290	11.1
NMC-PC4UD55B-020-GY	U/UTP	5e	2.0	0.000317	0.081	10 pcs.	0.003168	0.805	160 pcs.	520x420x290	13.9
NMC-PC4UD55B-030-GY	U/UTP	5e	3.0	0.000422	0.106	10 pcs.	0.004224	1.062	120 pcs.	520x420x290	13.7
NMC-PC4UD55B-050-GY	U/UTP	5e	5.0	0.000634	0.183	10 pcs.	0.006336	1.825	80 pcs.	520x420x290	15.6
NMC-PC4UD55B-075-GY	U/UTP	5e	7.5	0.001266	0.266	10 pcs.	0.012664	2.655	40 pcs.	520x420x290	11.6
NMC-PC4UD55B-100-GY	U/UTP	5e	10.0	0.001448	0.351	10 pcs.	0.014480	3.506	35 pcs.	520x420x290	13.3
NMC-PC4UD55B-150-GY	U/UTP	5e	15.0	0.003128	0.510	10 pcs.	0.031281	5.100	25 pcs.	520x420x290	13.1
NMC-PC4UD55B-200-GY	U/UTP	5e	20.0	0.003255	0.605	10 pcs.	0.032551	6.050	15 pcs.	520x420x290	14.2